

## Decorative Wall Coating



V-CORE (Pty) Ltd  
21-23 Wimbledon Road  
Blackheath  
7580 Cape Town  
Western Cape Province  
South Africa

Tel: +27 (0)21 9059758  
www.v-core.co.za  
info@v-core.co.za

## VERMICUCOTE Benefits | *Ten reasons to buy*

1. Vermiculite is a natural mineral.
2. Vermiculite is 100% environmentally friendly.
3. Vermiculite is insulating and fireproof.
4. The wall will have a natural and highly attractive look and feel.
5. Specially developed Vermiculite by V-Core to optimize the result.
6. Customizable wall colour.
7. Easy to apply.
8. Specially formulated 4x component system.
9. System professionally developed by a reputed paint specialist.
10. Proudly South African.

## VERMICUCOTE Product Details | *Green and Natural*



<b>4 Component System:</b>	<b>Primer, Binder, Vermiculite, Glaze</b>
<b>Application time:</b>	<b>3- 5 days</b>
<b>Lead Time:</b>	<b>10 working days</b>
<b>Available Colors:</b>	<b>Natural Gold / Brown Standard Colors Special Colors on request</b>

## Decorative Wall Coating



### Application Instructions Health and Safety Precautions

#### Application Instructions

- ✓ Coarse aggregate primer comes tinted to a similar colour to Vermiculite.
- ✓ Apply 1x coat of coarse aggregate primer with a roller.
- ✓ Spread of primer per coat is 4m<sup>2</sup> per litre – let it dry overnight.
- ✓ Mix the Binder with the Vermiculite on site.
- ✓ 5l of binder is added to 15l of Vermiculite. Stir the Vermiculite Mix.
- ✓ Apply by trowel to the dry primer surface – spread of Vermiculite mix is 3m<sup>2</sup>.
- ✓ Allow to dry 3 to 5 days subject to ambient temperature.
- ✓ Apply 2x coats of the Hydroglace in the desired colour.
- ✓ The spread per litre Hydroglace is 8m<sup>2</sup> per coat.

#### Health and Safety Precautions

- ✓ Wear plastic or rubber gloves.
- ✓ If contact with skin or eyes, rinse with plenty of water.

**Vermiculite • Proudly South African!**